



| DN | Frame outside $\varnothing d$ | $\varnothing k$ | $\varnothing D$ | L | n | $\varnothing d2$ |
|------|-------------------------------|-----------------|-----------------|-----|----|------------------|
| 400 | 406,4 | 466 | 507 | 160 | 12 | 15 |
| 500 | 508 | 568 | 608 | 160 | 16 | 15 |
| 600 | 610 | 670 | 710 | 160 | 16 | 15 |
| 700 | 711 | 770 | 811 | 200 | 20 | 15 |
| 800 | 813 | 873 | 913 | 200 | 24 | 15 |
| 900 | 914 | 974 | 1014 | 200 | 24 | 15 |
| 1000 | 1016 | 1076 | 1116 | 200 | 28 | 15 |
| 1100 | 1120 | 1190 | 1240 | 200 | 28 | 19 |
| 1200 | 1220 | 1290 | 1340 | 200 | 32 | 19 |
| 1300 | 1320 | 1390 | 1440 | 200 | 32 | 19 |
| 1400 | 1420 | 1490 | 1540 | 200 | 36 | 19 |
| 1500 | 1520 | 1610 | 1680 | 200 | 36 | 24 |
| 1600 | 1620 | 1710 | 1780 | 240 | 40 | 24 |
| 1700 | 1720 | 1810 | 1880 | 240 | 40 | 24 |
| 1800 | 1820 | 1910 | 1980 | 240 | 44 | 24 |
| 1900 | 1920 | 2010 | 2080 | 240 | 44 | 24 |
| 2000 | 2020 | 2110 | 2180 | 240 | 48 | 24 |
| 2100 | 2120 | 2210 | 2280 | 300 | 48 | 24 |
| 2200 | 2220 | 2310 | 2380 | 300 | 52 | 24 |
| 2300 | 2320 | 2410 | 2480 | 300 | 52 | 24 |
| 2400 | 2420 | 2510 | 2580 | 300 | 56 | 24 |
| 2500 | 2520 | 2630 | 2720 | 300 | 56 | 24 |
| 2600 | 2620 | 2730 | 2820 | 300 | 60 | 24 |
| 2700 | 2720 | 2830 | 2920 | 300 | 60 | 24 |
| 2800 | 2820 | 2930 | 3020 | 300 | 64 | 24 |
| 3000 | 3020 | 3130 | 3220 | 300 | 68 | 24 |

Remarks:

- Standard damper connection by welding. Flange connection as option.
- Dimensions are only informative. Final dimensions according to design data.