



DN	Frame outside $\varnothing d$	$\varnothing k$	$\varnothing D$	L	n	$\varnothing d2$
400	406,4	466	507	160	12	15
500	508	568	608	160	16	15
600	610	670	710	160	16	15
700	711	770	811	200	20	15
800	813	873	913	200	24	15
900	914	974	1014	200	24	15
1000	1016	1076	1116	200	28	15
1100	1120	1190	1240	200	28	19
1200	1220	1290	1340	200	32	19
1300	1320	1390	1440	200	32	19
1400	1420	1490	1540	200	36	19
1500	1520	1610	1680	200	36	24
1600	1620	1710	1780	240	40	24
1700	1720	1810	1880	240	40	24
1800	1820	1910	1980	240	44	24
1900	1920	2010	2080	240	44	24
2000	2020	2110	2180	240	48	24
2100	2120	2210	2280	300	48	24
2200	2220	2310	2380	300	52	24
2300	2320	2410	2480	300	52	24
2400	2420	2510	2580	300	56	24
2500	2520	2630	2720	300	56	24
2600	2620	2730	2820	300	60	24
2700	2720	2830	2920	300	60	24
2800	2820	2930	3020	300	64	24
3000	3020	3130	3220	300	68	24

Remarks:

- Standard damper connection by welding. Flange connection as option.
- Dimensions are only informative. Final dimensions according to design data.